NSN 5905-00-430-5344

Film Fixed Resistor - Page 1 of 1

A001a0



View Online at https://aerobasegroup.com/nsn/5905-00-430-5344

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
|--|
| -100.0/+100.0 |
| Electrical Resistance: |
| 78.410 ohms |
| Resistance Tolerance In Percent: |
| -0.250/+0.250 |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 125.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 175.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| -65.0/+175.0 |
| Inclosure Method: |
| Encapsulated |
| Terminal Type: |
| Wire lead |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 1.500 inches |
| Body Diameter: |
| 0.100 inches |
| Body Length: |
| 0.300 inches |
| Power Dissipation Rating In Watts: |
| 0.125 free air |
| End Application: |
| Tarawa class lha, nimitz class cvn, spruance class dd (963), whidbey island class lsd, safeguard class ars, virginia class cgn (41), |
| forrestal class cv, supply class aoe, austin ship class lpd-4 amphibious transport docks. |
| Criticality Code Justification: |
| Feat |
| Special Features: |
| Weapon system essetial |
| Style Designator: |
| Axial terminal each end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |