NSN 5905-00-430-6271

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-430-6271

Continu Countitus
Section Quantity:
1
Body Style:
Cylindrical
Reliability Indicator:
Not established
Overall Length:
0.469 inches
Terminal Length:
0.188 inches
Body Diameter:
0.266 inches
Body Length:
0.281 inches
Overall Diameter:
0.266 inches
Actuator Type:
Flush drive with slot-hole
Center To Center Distance Between Terminals:
0.220 inches
Terminal Location:
Radially positioned over more than half the circumference
Mounting Method:
Terminal
Electrical Resistance Per Section:
200.0 kilohms single section
Center To Center Distance Between Center Terminal And Outside Terminal:
0.110 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0 to 100.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:

3 pin

NSN 5905-00-430-6271

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Sneif Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A002a0