NSN 5905-00-431-3651

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-431-3651

Section Quantity:
1
Body Style:
Cylindrical servo mounted
Pilot Diameter:
0.96880 inches
Pilot Length:
0.06700 inches
Overall Length:
1.447 inches
Undercut Diameter:
0.968 inches
Undercut Width:
0.05700 inches
Body Diameter:
1.094 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.750 inches
Body Length:
0.666 inches
Overall Diameter:
1.234 inches
Mounting Lip Diameter:
1.09400 inches
Mounting Lip Depth:
0.06200 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 68.0 and 70.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:

300.000 ohms single section

NSN 5905-00-431-3651 Precision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
90.0
Function Conformity Tolerance Per Section:
-2.00/+2.00 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.3/+3.3 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
148.9 single section
Test Data Document:
05624-nylc1229 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A002a0