NSN 5905-00-431-5136

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-431-5136

20.0/420.0 Electrical Resistance: 18.700 ohms Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Diameter: 0.094 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Await terminal each end
Resistance Tolerance In Percent: 4.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Write lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.004 inches Body Diameter: 0.094 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Resistance Tolerance In Percent: 4.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Pailure Rate Level In Percent: 0.010 Body Diameter: 0.094 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Pailure Rate Level In Percent: 0.010 Body Diameter: 0.094 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Diameter: 0.094 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Diameter: 0.094 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Diameter: 0.094 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Diameter: 0.094 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Diameter: 0.094 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Diameter: 0.094 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Diameter: 0.094 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Diameter: 0.094 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Diameter: 0.094 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Diameter: 0.094 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Established Reliability Failure Rate Level In Percent: 0.010 Body Diameter: 0.094 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Reliability Failure Rate Level In Percent: 0.010 Body Diameter: 0.094 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Body Diameter: 0.094 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Body Diameter: 2.094 inches Body Length: 2.406 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
2.094 inches Body Length: 2.406 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Body Length: 0.406 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
2.406 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end
2.000 free air Style Designator: Axial terminal each end
Style Designator: Axial terminal each end
Axial terminal each end
Test Data Document:
31349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A001a0