

View Online at <https://aerobasegroup.com/nsn/5905-00-433-5862>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

1.208 inches

Body Diameter:

0.500 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.500 inches

Mounting Bushing Length:

0.250 inches

Body Length:

0.469 inches

Overall Diameter:

0.500 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

295.0

Maximum Starting Torque:

3.00 inch-ounces

Maximum Running Torque:

0.50 inch-ounces

Maximum Stop Torque:

64.00 inch-ounces

Nonturn Device Location:

At 5: 00 oclock and at 11: 00 oclock

Nonturn Device Radius:

0.245 inches

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Rear end

Mounting Method:

Standard bushing

Features Provided:

Nonmetallic shaft

Electrical Resistance Per Section:

500.0 ohms single section

Rotary Actuator Travel In Angular Deg:

295.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

C single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0