Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-434-1556

### Section Quantity:

1

Body Style:

Cylindrical

**Reliability Indicator:** 

Not established

#### **Overall Length:**

0.357 inches

Terminal Length:

0.187 inches

Body Diameter:

#### 0.250 inches

Body Length:

#### 0.180 inches

**Overall Diameter:** 

# 0.250 inches

Actuator Type:

Flush drive with slot-hole

### Effective Electrical Rotation In Deg Angular Rotation:

240.0

#### Maximum Starting Torque:

5.00 inch-ounces

### Center To Center Distance Between Terminals:

0.200 inches

#### **Terminal Location:**

Rear end

#### **Mounting Method:**

Terminal

#### **Electrical Resistance Per Section:**

500.0 ohms single section

#### Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

### Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0 to 100.0 single section

# Power Dissipation Rating Per Section In Watts:

0.5 free air single section

### **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

# Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:

A single section

### Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

### Unit Of Measure:

---

### Demilitarization:

No

Fiig:

A002a0