NSN 5905-00-434-1642

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-434-1642

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-260.0/+260.0
Electrical Resistance:
5.100 kilohms
Resistance Tolerance In Percent:
-5.000/+5.000
Fixed Tap Quantity:
1
Ambient Tempurature In Deg Celsius At Full Rated Power:
25.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
350.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+350.0
Inclosure Method:
Encapsulated
Terminal Type:
Ferrule
Reliability Indicator:
Not established
Terminal Length:
0.500 inches
Body Diameter:
1.125 inches
Body Length:
9.625 inches
Power Dissipation Rating In Watts:
151.200 free air
Section Resistance:
2.550 kilohms
Fixed Tap Terminal Type:
Tab, solder lug
Style Designator:
Axial terminal each end
Test Data Document:
81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-r-26/1a government specification
Shelf Life:
N/2

--

Unit Of Measure:

NSN 5905-00-434-1642

Inductive Wire Wound Fixed Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A001a0