## NSN 5905-00-434-5414

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-434-5414

Section Quantity:
1
Body Style:
Cylindrical
Reliability Indicator:
Not established
Terminal Length:
0.187 inches
Body Diameter:
0.270 inches
Body Length:
0.276 inches
Actuator Type:
Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
Between 240.0 and 300.0
Maximum Starting Torque:
3.00 inch-ounces
Maximum Running Torque:
3.00 inch-ounces
Center To Center Distance Between Terminals:
0.200 inches
Terminal Location:
Lower adjacent side two rows
Mounting Method:
Terminal
Center To Center Distance Between Terminal Rows:
0.100 inches
Electrical Resistance Per Section:
50.000 ohms single section
Rotary Actuator Travel In Angular Deg:
Between 240.0 and 300.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-25.0 to 25.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:

-20.0 to 20.0 single section

## NSN 5905-00-434-5414

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:
Continuous motion
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No