Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-434-5416

Section	Quantity:
1	
Body St	yle:
Cylindric	al
Reliabil	ty Indicator:
Not esta	blished
Overall	Length:
0.469 in	ches
Termina	I Length:
0.188 in	ches
Body Di	ameter:
Betweer	0.230 inches and 0.270 inches
Body Le	ength:
Betweer	0.205 inches and 0.235 inches
Overall	Diameter:
0.270 in	ches
Actuato	r Туре:
Flush dr	ve with slot-hole
Effectiv	e Electrical Rotation In Deg Angular Rotation:
360.0	
Center ⁻	Fo Center Distance Between Terminals:
0.200 in	ches
Fragility	Factor:
Moderat	ely delicate
Termina	I Location:
Rear en	t de la construcción de la const
Mountir	g Method:
Termina	
Feature	s Provided:
Humidity	y proof
Electric	al Resistance Per Section:
250.000	ohms single section
Center ⁻	o Center Distance Between Center Terminal And Outside Terminal:
0.100 in	ches
Ambien	t Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 sii	ngle section
Tempur	ature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0 to	100.0 single section
	Dissipation Rating Per Section In Watts:
	air single section
Resista	nce Tolerance Per Section In Percent:

NSN 5905-00-434-5416

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:

Continuous motion

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0