NSN 5905-00-434-8748

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-434-8748

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -100.0/+100.0 Electrical Resistance: 20.000 kilohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.093 inches Body Length: 0.260 inches Power Dissipation Rating In Watts: 0.100 free air Test Data Document: 13499-705-1470 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer dra	
Electrical Resistance: 20.000 kilohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.093 inches Body Length: 0.260 inches Power Dissipation Rating In Watts: 0.100 free air Test Data Document:	
20,000 kilohms Resistance Tolerance In Percent: -1,000/+1,000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.093 inches Body Length: 0.260 inches Power Dissipation Rating In Watts: 0.100 free air Test Data Document:	
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.093 inches Body Length: 0.260 inches Power Dissipation Rating In Watts: 0.100 free air Test Data Document:	
-1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.093 inches Body Length: 0.260 inches Power Dissipation Rating In Watts: 0.100 free air Test Data Document:	
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.093 inches Body Length: 0.260 inches Power Dissipation Rating In Watts: 0.100 free air Test Data Document:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.093 inches Body Length: 0.260 inches Power Dissipation Rating In Watts: 0.100 free air Test Data Document:	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.093 inches Body Length: 0.260 inches Power Dissipation Rating In Watts: 0.100 free air Test Data Document:	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.093 inches Body Length: 0.260 inches Power Dissipation Rating In Watts: 0.100 free air Test Data Document:	
-55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.093 inches Body Length: 0.260 inches Power Dissipation Rating In Watts: 0.100 free air Test Data Document:	
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.093 inches Body Length: 0.260 inches Power Dissipation Rating In Watts: 0.100 free air Test Data Document:	
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.093 inches Body Length: 0.260 inches Power Dissipation Rating In Watts: 0.100 free air Test Data Document:	
Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.093 inches Body Length: 0.260 inches Power Dissipation Rating In Watts: 0.100 free air Test Data Document:	
Wire lead Reliability Indicator: Not established Body Diameter: 0.093 inches Body Length: 0.260 inches Power Dissipation Rating In Watts: 0.100 free air Test Data Document:	
Reliability Indicator: Not established Body Diameter: 0.093 inches Body Length: 0.260 inches Power Dissipation Rating In Watts: 0.100 free air Test Data Document:	
Not established Body Diameter: 0.093 inches Body Length: 0.260 inches Power Dissipation Rating In Watts: 0.100 free air Test Data Document:	
Body Diameter: 0.093 inches Body Length: 0.260 inches Power Dissipation Rating In Watts: 0.100 free air Test Data Document:	
0.093 inches Body Length: 0.260 inches Power Dissipation Rating In Watts: 0.100 free air Test Data Document:	
Body Length: 0.260 inches Power Dissipation Rating In Watts: 0.100 free air Test Data Document:	
0.260 inches Power Dissipation Rating In Watts: 0.100 free air Test Data Document:	
Power Dissipation Rating In Watts: 0.100 free air Test Data Document:	
0.100 free air Test Data Document:	
Test Data Document:	
13499-705-1470 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing)	
	ing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A001a0	