NSN 5905-00-434-8858

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-434-8858

Section Quantity:
1
Body Style:
Cylindrical
Reliability Indicator:
Not established
Overall Length:
1.078 inches
Terminal Length:
0.547 inches
Body Diameter:
0.500 inches
Body Length:
0.531 inches
Overall Diameter:
0.500 inches
Actuator Type:
Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
295.0
Maximum Stop Torque:
64.00 inch-ounces
Center To Center Distance Between Terminals:
0.200 inches
Terminal Location:
Rear end
Mounting Method:
Terminal
Electrical Resistance Per Section:
15.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
295.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Resistance Tempurature Characteristic Range Per Section In Percent:
$-0.0\ to\ 7.0\ -55\ degrees\ celsius\ single\ section\ and\ -0.0\ to\ 3.5\ -25\ degrees\ celsius\ single\ section\ and\ -0.0\ to\ 2.0\ 0\ degrees\ celsius\ single\ section\ and\ -0.0\ to\ 2.0\ 0\ degrees\ celsius\ single\ section\ and\ -0.0\ to\ 2.0\ 0\ degrees\ celsius\ single\ section\ and\ -0.0\ to\ 2.0\ 0\ degrees\ celsius\ single\ section\ and\ -0.0\ to\ 2.0\ 0\ degrees\ celsius\ single\ section\ and\ -0.0\ to\ 2.0\ 0\ degrees\ celsius\ single\ section\ and\ -0.0\ to\ 2.0\ 0\ degrees\ celsius\ single\ section\ and\ -0.0\ to\ 2.0\ 0\ degrees\ celsius\ single\ section\ and\ -0.0\ to\ 2.0\ 0\ degrees\ celsius\ single\ section\ and\ -0.0\ to\ 2.0\ 0\ degrees\ celsius\ single\ section\ and\ -0.0\ to\ 2.0\ 0\ degrees\ celsius\ single\ section\ and\ -0.0\ to\ 2.0\ 0\ degrees\ celsius\ single\ section\ and\ -0.0\ to\ 2.0\ 0\ degrees\ celsius\ single\ section\ and\ -0.0\ to\ 2.0\ 0\ degrees\ celsius\ single\ section\ and\ -0.0\ to\ 2.0\ 0\ degrees\ celsius\ single\ section\ and\ -0.0\ to\ 2.0\ 0\ degrees\ celsius\ single\ section\ and\ -0.0\ to\ 2.0\ 0\ degrees\ celsius\ single\ section\ and\ -0.0\ to\ 2.0\ 0\ degrees\ celsius\ single\ section\ and\ -0.0\ to\ 2.0\ t$
section and -0.0 to 0.0 25 degrees celsius single section and -2.5 to 2.5 85 degrees celsius single section and -0.0 to 5.5 120 degrees
celsius single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:

-10.0 to 10.0 single section

0.5 heat sink single section

Resistance Tolerance Per Section In Percent:

NSN 5905-00-434-8858

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:	
Stops	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
70.0 single section	
Standard Taper Curve Per Section:	
A single section	
Terminal Type And Quantity:	
3 pin	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
No	
Filg:	