NSN 5905-00-435-2026

Section Quantity:

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-435-2026

1
Body Style:
Rectangular w/mounting holes/slots
Overall Length:
1.060 inches
Terminal Length:
0.200 inches
Overall Height:
0.560 inches
Overall Width:
0.280 inches
Mounting Hole Diameter:
0.088 inches
Shaft Diameter:
0.100 inches
Shaft Length:
0.060 inches
Body Length:
1.000 inches
Body Width:
0.280 inches
Body Height:
0.360 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Center To Center Distance Between Terminals:
0.500 inches
Lateral Distance Between Mounting Hole Centers:
0.830 inches
Mounting Facility Quantity:
2
Terminal Location:
Lower adjacent side two rows
Mounting Method:
Unthreaded hole
Center To Center Distance Between Terminal Rows:
0.200 inches
Flactrical Resistance Per Section:

200.000 kilohms single section

NSN 5905-00-435-2026

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:	
5400.0	
Center To Center Distance Between Center Terminal And Outside Terminal:	
0.200 inches	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
85.0 single section	
Power Dissipation Rating Per Section In Watts:	
0.2 free air single section	
Resistance Tolerance Per Section In Percent:	
-20.0 to 20.0 single section	
Actuator Travel Control Feature:	
Clutch	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
25.0 single section	
Standard Taper Curve Per Section:	
A single section	
Terminal Type And Quantity:	
3 pin	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A002a0	