Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-436-1964

## Section Quantity:

1

Body Style:

Rectangular

## **Reliability Indicator:**

Not established

#### **Terminal Length:**

0.160 inches

#### Shaft Diameter:

0.100 inches

#### Shaft Length:

0.100 inches

#### Body Length:

0.750 inches

#### Body Width:

## 0.160 inches

## Body Height:

0.310 inches

# Shaft Style:

Round, slotted

## Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

7200.0

#### **Center To Center Distance Between Terminals:**

0.500 inches

#### **Terminal Location:**

Lower adjacent side two rows

#### **Mounting Method:**

Terminal

#### Center To Center Distance Between Terminal Rows:

0.100 inches

#### **Electrical Resistance Per Section:**

10.0 kilohms single section

#### Rotary Actuator Travel In Angular Deg:

7200.0

## Center To Center Distance Between Center Terminal And Outside Terminal:

0.200 inches

#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

## Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-250.0 to 250.0 single section

# NSN 5905-00-436-1964 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:

0.75 free air single section

## **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

## Actuator Travel Control Feature:

Clutch

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

## Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

#### Unit Of Measure:

---

## Demilitarization:

No

#### Fiig:

A002a0