Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-437-4075

# Section Quantity:

1

- Body Style:
- Cylindrical w/readout
- Reliability Indicator:
- Not established
- **Overall Length:**
- 2.470 inches
- **Body Diameter:**
- 1.375 inches
- Mounting Bushing Length:
- 0.375 inches
- Body Length:
- 2.015 inches
- **Overall Diameter:**
- 1.750 inches
- Actuator Type:
- Integral knob with counter

### Effective Electrical Rotation In Deg Angular Rotation:

3600.0

- Maximum Starting Torque:
- 15.00 inch-ounces
- Maximum Running Torque:
- 15.00 inch-ounces

#### Maximum Stop Torque:

48.00 inch-ounces

#### Screw Thread Diameter:

0.250 inches

#### Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

**Terminal Location:** 

Rear end

## Mounting Method:

Standard bushing

## **Electrical Resistance Per Section:**

100.000 ohms single section

# Rotary Actuator Travel In Angular Deg:

3600.0

## Function Conformity Tolerance Per Section:

-0.20/+0.20 single section



Ambier	nt Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
	ngle section
	Oissipation Rating Per Section In Watts:
	air single section
	on Conformity Per Section:
	section independent linearity
-	ance Tolerance Per Section In Percent:
-3.0/+3.	0 single section
	or Travel Control Feature:
Stops	
Functio	on Characteristic Per Section:
Single s	section linear
Tempu	rature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+2	20.0 single section
Ambier	nt Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 sin	ngle section
Preciou	us Material And Location:
Termina	als gold
Preciou	us Material:
Gold	
Termina	al Type And Quantity:
3 wire lo	оор
Shelf Li	ife:
N/a	
Unit Of	Measure:
Demilit	arization:
No	
Fiig:	
	)