NSN 5905-00-437-9580

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-437-9580

Indepty Control of
Resistance Tolerance In Percent: 0.030/+0.030 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Note established Terminal Length: 1.000 inches 30dy Diameter: 0.141 inches 30dy Length: 0.391 inches Power Dissipation Rating In Watts: 1.000 free air
Resistance Tolerance In Percent: 0.030/+0.030 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.000 inches Body Diameter: 0.141 inches Body Length: 0.391 inches Power Dissipation Rating In Watts: 1.010 free air
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.000 inches Body Diameter: 0.1411 inches Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 nclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.000 inches 30dy Diameter: 0.141 inches 30dy Length: 0.391 inches Power Dissipation Rating In Watts:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.000 inches Body Diameter: 0.141 inches Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: 1.000 inches 30dy Diameter: 0.141 inches 30dy Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air
Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: 1.000 inches Body Diameter: 2.141 inches Body Length: 2.391 inches Power Dissipation Rating In Watts: 2.100 free air
Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: 1.000 inches Body Diameter: 0.141 inches Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: 1.000 inches Body Diameter: 0.141 inches Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: 1.000 inches Body Diameter: 0.141 inches Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: 1.000 inches Body Diameter: 0.141 inches Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air
Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: 1.000 inches Body Diameter: 0.141 inches Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air
Wire lead Reliability Indicator: Not established Ferminal Length: 1.000 inches Body Diameter: 0.141 inches Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air
Reliability Indicator: Not established Ferminal Length: 1.000 inches Body Diameter: 0.141 inches Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air
Not established Ferminal Length: 1.000 inches Body Diameter: 0.141 inches Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air
Terminal Length: 1.000 inches Body Diameter: 0.141 inches Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air
1.000 inches Body Diameter: 0.141 inches Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air
Body Diameter: 0.141 inches Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air
0.141 inches Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air
Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air
0.391 inches Power Dissipation Rating In Watts: 0.100 free air
Power Dissipation Rating In Watts: 0.100 free air
0.100 free air
Node Designators
Style Designator:
Axial terminal each end
Fest Data Document:
06481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg:
A001a0