

View Online at <https://aerobasegroup.com/nsn/5905-00-441-0630>

**Section Quantity:**

2

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

0.9688 inches

**Pilot Length:**

0.0620 inches

**Undercut Diameter:**

1.062 inches

**Undercut Width:**

0.0620 inches

**Body Diameter:**

1.072 inches

**Shaft Diameter:**

0.125 inches

**Shaft Length:**

1.000 inches

**Body Length:**

1.072 inches

**Mounting Lip Diameter:**

1.0620 inches

**Mounting Lip Depth:**

0.0620 inches

**Shaft Style:**

Round

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

150.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Clamp ring

**Features Provided:**

Humidity proof

**Electrical Resistance Per Section:**

25.000 kilohms all sections

**Rotary Actuator Travel In Angular Deg:**

150.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

71.0 all sections

**Power Dissipation Rating Per Section In Watts:**

2.1 free air 1st section

**Resistance Tolerance Per Section In Percent:**

-2.0 to 2.0 all sections

**Actuator Travel Control Feature:**

Stops

**Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:**

-20.0 to 20.0 all sections

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

30.0 all sections

**Standard Taper Curve Per Section:**

A all sections

**Terminal Type And Quantity:**

6 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0