## NSN 5905-00-441-2889

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-441-2889 **Section Quantity: Reliability Indicator:** Not established **Mounting Hole Diameter:** Between 0.187 inches and 0.191 inches **Body Length:** 0.640 inches **Body Width:** 4.420 inches **Body Height:** 4.420 inches **Actuator Type:** Flush drive with slot-hole **Maximum Starting Torque:** 15.00 inch-ounces **Maximum Running Torque:** 15.00 inch-ounces **Fragility Factor:** Moderately rugged **Mounting Facility Quantity:** 4 **Mounting Method:** Unthreaded hole **Features Provided:** Humidity proof **Electrical Resistance Per Section:** 2.5 kilohms all sections **Function Conformity Tolerance Per Section:** -1.00/+1.00 2nd section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 all sections **Power Dissipation Rating Per Section In Watts:** 1.0 free air all sections **Function Conformity Per Section:** 2nd section independent linearity **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 all sections **Function Characteristic Per Section:** 

2nd section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 all sections

## NSN 5905-00-441-2889

Precision Wire Wound Variable Resistor - Page 2 of 2



Terminal	Type	And	Quantity:
----------	------	-----	-----------

2 tab, solder lug and 4 turret

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0