NSN 5905-00-441-7477

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-441-7477 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.500 inches **Shaft Diameter:** 0.625 inches **Shaft Length:** 0.828 inches **Mounting Bushing Length:** 0.450 inches **Body Length:** 0.297 inches **Shaft Style:** Round, slotted, undercut **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 340.0 **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** 0.500 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 350.500 kilohms single section

Rotary Actuator Travel In Angular Deg: 340.0

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

NSN 5905-00-441-7477

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:
Stops
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0