Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-442-5059

# Section Quantity:

1

Body Style:

Rectangular w/mounting holes

# **Reliability Indicator:**

Not established

### Mounting Hole Diameter:

0.088 inches

**Body Length:** 

0.375 inches

- **Body Width:**
- 0.203 inches

**Body Height:** 

#### 0.375 inches

Actuator Type:

#### Flush drive with slot-hole

### Effective Electrical Rotation In Deg Angular Rotation:

9000.0

### Lateral Distance Between Mounting Hole Centers:

0.419 inches

## **Mounting Facility Quantity:**

2

#### **Terminal Location:**

Rear end

#### Mounting Method:

Unthreaded hole

#### **Electrical Resistance Per Section:**

50.0 kilohms single section

## **Rotary Actuator Travel In Angular Deg:**

9000.0

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

## Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0 to 100.0 single section

## Power Dissipation Rating Per Section In Watts:

0.5 free air single section

### **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

### **Actuator Travel Control Feature:**

Clutch

#### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

AeroBase Group

Standard Taper Curve Per Section:

A single section

# Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A002a0