

View Online at <https://aerobasegroup.com/nsn/5905-00-442-5070>

**Section Quantity:**

2

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

Between 0.7450 inches and 0.7550 inches

**Pilot Length:**

Between 0.0570 inches and 0.0620 inches

**Undercut Diameter:**

0.750 inches

**Undercut Width:**

0.0620 inches

**Body Diameter:**

0.875 inches

**Shaft Diameter:**

0.125 inches

**Shaft Length:**

0.448 inches

**Body Length:**

1.000 inches

**Mounting Lip Diameter:**

Between 0.8700 inches and 0.8800 inches

**Mounting Lip Depth:**

0.0620 inches

**Shaft Style:**

Round

**Shaft Bearing Type:**

Ball

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

327.0

**Maximum Starting Torque:**

1.00 inch-ounces

**Maximum Running Torque:**

0.02 inch-ounces

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Clamp ring

**Electrical Resistance Per Section:**

2.500 kilohms all sections

**Rotary Actuator Travel In Angular Deg:**

322.0

**Function Conformity Tolerance Per Section:**

-2.00/+2.00 all sections

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

165.0 all sections

**Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-20.0/+20.0 all sections

**Power Dissipation Rating Per Section In Watts:**

2.0 free air all sections

**Function Conformity Per Section:**

All sections independent linearity

**Resistance Tolerance Per Section In Percent:**

-1.0/+1.0 all sections

**Actuator Travel Control Feature:**

Stops

**Function Characteristic Per Section:**

All sections linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

60.0 all sections

**Terminal Type And Quantity:**

6 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0