

View Online at <https://aerobasegroup.com/nsn/5905-00-442-5187>

Section Quantity:

1

Body Style:

Cylindrical

Reliability Indicator:

Not established

Terminal Length:

0.200 inches

Body Diameter:

0.516 inches

Body Length:

0.313 inches

Actuator Type:

Flush drive with slot-hole

Effective Electrical Rotation In Deg Angular Rotation:

360.0

Center To Center Distance Between Terminals:

0.200 inches

End Application:

Los angeles class ssn (688); missile, all-weather antiship, harpoon (agm-84); kidd class ddg; communications terminal, satellite an/gsc-3 (v)1; sturgeon class ssn (637); oliver perry class ffg; nimitz class cv; spruance class dd (963); virginia class cgn (41)

Terminal Location:

Right adjacent side two rows

Mounting Method:

Terminal

Center To Center Distance Between Terminal Rows:

0.100 inches

Electrical Resistance Per Section:

10.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

360.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-70.0 to 70.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Actuator Travel Control Feature:

Continuous motion

Criticality Code Justification:

Feat

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Special Features:

Weapon system essential

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0