NSN 5905-00-443-8905

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-443-8905

Electrical Resistance: 45.300 kilohms Resistance Tolerance In Percent: 41.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter:
Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter:
Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 nclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter:
Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter:
Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter:
55.0/+175.0 nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter:
Incapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter:
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter:
Ferminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter:
Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter:
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter:
Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter:
Reliability Failure Rate Level In Percent: 0.001 Body Diameter:
0.001 Body Diameter:
Body Diameter:
) 250 inches
7.200 III01103
Body Length:
0.750 inches
Power Dissipation Rating In Watts:
0.500 free air
Style Designator:
Axial terminal each end
Test Data Document:
31349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Fiig:
A001a0