Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-443-9489

Section Quantity:

1

Body Style:

Rectangular w/mounting holes

Reliability Indicator:

Not established

Overall Length:

0.535 inches

Overall Height:

0.500 inches

Overall Width:

0.187 inches

Mounting Hole Diameter:

0.093 inches

Shaft Diameter:

0.075 inches

Shaft Length:

0.035 inches

Body Length:

0.500 inches

Body Width:

0.187 inches

Body Height:

0.500 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Maximum Starting Torque:

5.00 inch-ounces

Lateral Distance Between Mounting Hole Centers:

0.520 inches

Mounting Facility Quantity:

2

Terminal Location:

Rear end

Mounting Method:

Unthreaded hole

Features Provided:

Nonmetallic shaft

Electrical Resistance Per Section:

2.000 kilohms single section

NSN 5905-00-443-9489

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:

9000.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0 to 50.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0