NSN 5905-00-444-0325

Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-444-0325

S2.000 kilohms Resistance Tolerance In Percent: -0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Uninclosed Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator:
Electrical Resistance: 52.000 kilohms Resistance Tolerance In Percent: -0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Uninclosed Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator: Not established
Resistance Tolerance In Percent: -0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Uninclosed Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator:
-0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Uninclosed Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Uninclosed Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Uninclosed Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Uninclosed Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Uninclosed Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Uninclosed Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator:
Inclosure Method: Uninclosed Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator:
Inclosure Method: Uninclosed Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator:
Uninclosed Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator:
Terminal Type: Wire lead Reactance Characteristic: Noninductive Reliability Indicator:
Wire lead Reactance Characteristic: Noninductive Reliability Indicator:
Reactance Characteristic: Noninductive Reliability Indicator:
Noninductive Reliability Indicator:
Reliability Indicator:
Not established
Body Diameter:
0.105 inches
Body Length:
0.281 inches
Power Dissipation Rating In Watts:
0.050 free air
Style Designator:
Axial terminal each end
Test Data Document:
06481-912047 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.,
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0