NSN 5905-00-444-6647

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-444-6647

Section Quantity:
2

Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
1.125 inches

Shaft Length: 2.500 inches

Mounting Bushing Length:

0.375 inches

Shaft Diameter: 0.265 inches

Body Length:

0.625 inches

Undercut Diameter:

0.187 inches

Shaft Style:

Round, stepped

Actuator Type:

Dual concentric

Undercut Length:

1.250 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

.. .

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

10.0 kilohms 1st section

Power Dissipation Rating Per Section In Watts:

2.0 free air 1st section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 all sections

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 all sections

NSN 5905-00-444-6647

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:
A all sections
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0