Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-445-3727

# Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

## **Body Diameter:**

0.250 inches

### Shaft Diameter:

0.125 inches

Shaft Length:

0.250 inches

Mounting Bushing Length:

0.250 inches

Body Length:

## 0.744 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

7920.0

### Screw Thread Diameter:

0.216 inches

Screw Thread Series Designator:

Unf

Screw Thready Qty Per Inch (tpi):

28.0

### **Terminal Location:**

Rear end

### **Mounting Method:**

Standard bushing

### **Electrical Resistance Per Section:**

2.0 kilohms single section

## Rotary Actuator Travel In Angular Deg:

7920.0

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

## **Power Dissipation Rating Per Section In Watts:**

0.5 free air single section

## **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

# NSN 5905-00-445-3727

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

## **Special Features:**

2 flats 0.169 in. A/f nut 0.250 in. A/f

## Terminal Type And Quantity:

3 wire loop

Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A002a0