Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-448-0036

## Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

# Reliability Indicator:

Not established

#### **Overall Length:**

1.370 inches

#### **Overall Height:**

0.300 inches

#### **Overall Width:**

0.285 inches

Mounting Hole Diameter:

0.086 inches

#### Shaft Diameter:

# 0.125 inches

Shaft Length:

0.047 inches

# Body Length:

1.340 inches

# Body Width:

0.285 inches

#### Body Height:

0.300 inches

#### Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

# Effective Electrical Rotation In Deg Angular Rotation:

9000.0

# Maximum Starting Torque:

7.50 inch-ounces

# Lateral Distance Between Mounting Hole Centers:

1.000 inches

# **Mounting Facility Quantity:**

2

# Terminal Location:

Rear end

## **Mounting Method:**

Unthreaded hole

#### **Electrical Resistance Per Section:**

10.0 kilohms single section

# NSN 5905-00-448-0036

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



**Rotary Actuator Travel In Angular Deg:** 9000.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0 to 100.0 single section **Power Dissipation Rating Per Section In Watts:** 0.8 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Actuator Travel Control Feature:** Continuous motion Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 wire lead **Reference Number Differentiating Characteristics:** Quality controlled for polaris Shelf Life: Unit Of Measure: **Demilitarization:** 

No

---

N/a

Fiig:

A002a0