Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-448-2520

# Section Quantity:

1

Body Style:

Cylindrical

# **Reliability Indicator:**

Not established

#### **Body Diameter:**

0.750 inches

#### **Body Length:**

0.425 inches

#### Actuator Type:

Flush drive with slot-hole

## Effective Electrical Rotation In Deg Angular Rotation:

270.0

## Maximum Running Torque:

10.00 inch-ounces

## **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Tab

# **Electrical Resistance Per Section:**

4.0 kilohms single section

# Rotary Actuator Travel In Angular Deg:

270.0

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

## Power Dissipation Rating Per Section In Watts:

2.0 free air single section

## **Resistance Tolerance Per Section In Percent:**

-20.0 to 20.0 single section

## Actuator Travel Control Feature:

Stops

# Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

# Standard Taper Curve Per Section:

A single section

# Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

# Unit Of Measure:

---

# NSN 5905-00-448-2520

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A002a0