Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-448-3080

## Section Quantity:

1

# Body Style:

Rectangular w/mounting holes/slots

## **Reliability Indicator:**

Not established

#### **Overall Length:**

1.232 inches

#### **Overall Height:**

0.320 inches

#### **Overall Width:**

0.190 inches

#### Mounting Hole Diameter:

0.088 inches

#### Shaft Diameter:

## 0.115 inches

Shaft Length:

#### 0.070 inches

Body Length:

# 1.250 inches

Body Width:

#### 0.190 inches

**Body Height:** 

#### 0.320 inches

#### Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

7920.0

#### Maximum Starting Torque:

5.00 inch-ounces

#### Maximum Running Torque:

5.00 inch-ounces

#### Lateral Distance Between Mounting Hole Centers:

1.000 inches

# Mounting Facility Quantity:

2

# **Terminal Location:**

Rear end

# Mounting Method:

Unthreaded hole

# NSN 5905-00-448-3080

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
500.0 ohms single section
Rotary Actuator Travel In Angular Deg:
7920.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0 to 50.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0