Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-448-5537

Section Quantity: 1 1 2 dody Style: Rectangular Reliability Indicator: Established Reliability Faiture Rate Level In Percent: Established Reliability Faiture Rate Level In Percent: Common Com	
Rody Style:         Rectangular         Reliability Indicator:         Estabilished         Reliability Failure Rate Level In Percent:         0.100         Terminal Length:         0.172 inches         Shaft Diameter:         0.057 inches         Shaft Diameter:         0.075 inches         Shaft Length:         0.080 inches         Body Length:         0.375 inches         Body Vidth:         0.170 inches         Body Height:         0.420 inches         Botatorype:         Botatorype	
Rectangular         Reliability functions:         Established         Reliability Failure Rate Level In Percent:         0.100         Terminal Length:         0.172 inches         Shaft Diameter:         0.75 inches         Shaft Length:         0.080 inches         Body Length:         0.375 inches         Body Length:         0.375 inches         Body Length:         0.375 inches         Body Udith:         0.375 inches         Body Udith:         0.370 inches         Body Height:         0.470 inches         Body Height:         0.420 inches         Shaft Style:         Round, slotted         Actuator Type:         Single shaft         Effective Electrical Rotation In Deg Angular Rotation:         Louo Inches         Browen 5400.0 and 10800.0         Content Distance Between Terminals:         Lower adjacent side single row         Mouning Method:         Terminal         Elevienet S400.0 and 1080.0         Cater To Center Distance Between Center Terminal And Outside Terminal:         Lower adjace saction </td <td></td>	
Network         Established         Relability Failure Rate Level In Percent:         0.10         Terminal Length:         0.172 inches         Shaft Diameter:         0.075 inches         Shaft Length:         0.080 inches         Body Length:         0.375 inches         Body Length:         0.375 inches         Body Ungth:         0.375 inches         Body Vidth:         0.375 inches         Body Height:         0.420 inches         Body Height:         0.420 inches         Shaft Style:         Round, slotted         Actuator Type:         Single shaft         Effective Electrical Rotation In Deg Angular Rotation:         Between 5400.0 and 10800.0         Conter To Center Distance Between Terminals:         Icouring Method:         Terminal         Electrical Rosistance Per Section:         2.0 kolms single section         2.0 kolms single secti	
Established         Reliability Failure Rate Level In Percent:         0.100         Terminal Length:         0.172 inches         Shaft Janneter:         0.075 inches         Shaft Length:         0.075 inches         Body Length:         0.080 inches         Body Length:         0.375 inches         Body Width:         0.375 inches         Body Width:         0.370 inches         Body Beight:         0.420 inches         Shaft Length:         0.420 inches         Body Width:         0.420 inches         Body Solited         Actuator Type:         Single shaft         Effective Electrical Rotation In Deg Angular Rotation:         0.420 inches         Elevene S400.0 and 1080.0.0         Conter Distance Between Terminals:         0.200 inches         Terminal Location:         Lower adjacent side single row         Mounting Method:         2.0 kiloms single soction:         Co kiloms single soction:         Co kiloms single soction:         Co kiloms single soction:         Co kiloms single soction: <td>-</td>	-
Reliability Failure Rate Level In Percent:         0.100         Terminal Length:         0.172 inches         Shaft Diameter:         0.075 inches         Shaft Length:         0.080 inches         Bedy Length:         0.375 inches         Body Length:         0.375 inches         Body Width:         0.370 inches         Body Width:         0.370 inches         Body Height:         0.420 inches         Body Height:         0.420 inches         Body Jelght:         0.420 inches         Body Steted         Actuator Type:         Shaft Style:         Round, slotted         Actuator Type:         Single shaft         Effective Electrical Rotation In Deg Angular Rotation:         Between 5400.0 and 10800.0         Couten bistance Between Terminals:         0.200 inches         Terminal         Couter Distance Per Section:         2.04 kinhen single section         Chetrical Rosistance Per Section:         2.05 kinhens ingle section         Cottions single section         Cottions single section <t< td=""><td></td></t<>	
0.100         Terminal Length:         0.172 inches         Shaft Diameter:         0.075 inches         Shaft Length:         0.080 inches         Shaft Length:         0.080 inches         Body Length:         0.375 inches         Body Vidth:         0.376 inches         Body Height:         0.420 inches         Body Height:         0.420 inches         Shaft Style:         Round, slotted         Actuator Type:         Single shaft         Effective Electrical Rotation In Deg Angular Rotation:         Between 5400.0 and 10800.0         Center To Center Distance Between Terminals:         0.200 inches         Terminal Location:         Lower adjacent side single row         Mouting Method:         Terminal         Electrical Resistance Per Section:         2.0 kilohms single section         Rolay Actuator Travel In Angular Deg:         Between 5400.0 and 10800.0         Cherter Distance Between Center Terminal And Outside Terminal:         1.00 inches	
Ferninal Length:         0.172 inches         Shaft Diameter:         0.075 inches         Shaft Length:         0.080 inches         Body Length:         0.375 inches         Body Vength:         0.375 inches         Body Vength:         0.375 inches         Body Vength:         0.420 inches         Body Veight:         0.420 inches         Shaft Style:         Round, slotted         Actuator Type:         Single shaft         Effective Electrical Rotation In Deg Angular Rotation:         Rouwen S400.0 and 10800.0         Center To Center Distance Between Terminals:         0.200 inches         Terminal Location:         Lower adjacent side single row         Mounting Method:         Terminal         2.0 kilohms single section:         2.0 kilohms single section         Between 5400.0 and 10800.0	-
0.172 inches         Shaft Diameter:         0.075 inches         Shaft Length:         0.080 inches         Body Length:         0.375 inches         Body Vidth:         0.376 inches         Body Width:         0.170 inches         Body Height:         0.170 inches         Body Height:         0.420 inches         Shaft Style:         Round, sötted         Actuator Type:         Single shaft         Effective Electrical Rotation In Deg Angular Rotation:         Between 5400.0 and 10800.0         Center To Center Distance Between Terminals:         0.200 inches         Terminal Location:         Lower adjacent side single row         Mounting Method:         Terminal         Electrical Resistance Per Section:         2.0 kiloms single section         2.0 kiloms single section         2.0 kiloms single section:         2.0 kiloms single section         2.0 kiloms single section:         2.0 kiloms single section         Between 5400.0 and 10800.0	
Shaft Diameter:         0.075 inches         Shaft Length:         0.080 inches         Body Length:         0.375 inches         Body Width:         0.370 inches         Body Width:         0.170 inches         Body Height:         0.420 inches         Shaft Style:         Round, slotted         Actuator Type:         Single shaft         Effective Electrical Rotation In Deg Angular Rotation:         Between 5400.0 and 10800.0         Center To Center Distance Between Terminals:         0.200 inches         Terminal Location:         Lower adjacent side single row         Mounting Method:         2.02 kilohms single section         2.02 kilohms single section:         2.02 kilohms single section         2.02 kilohms single section         2.02 kilohms single section         2.02 kilohms single section:         2.02 kilohms single section         Between 5400.0 and 10800.0	-
0.075 inchesShaft Length:0.080 inchesBody Length:0.375 inchesBody Width:0.170 inchesBody Height:0.420 inchesShaft Style:Round, slottedActuator Type:Single shaftEffective Electrical Rotation In Deg Angular Rotation:Between 5400.0 and 10800.0Center To Center Distance Between Terminals:0.200 inchesErrinal Location:Lowar adjacent side single rowMounting Method:2.0 kilohms single section2.0 kilohms single section2.0 kilohms single section2.0 kilohms single section2.0 kilohms single sectionBetween 5400.0 and 10800.0Center To Center Distance Between Center Terminal And Outside Terminal:1.00 inches	
Shaft Length:0.080 inchesBody Length:0.375 inchesBody Width:0.170 inchesBody Height:0.420 inchesShaft Style:Round, slottedActuator Type:Single shaftEffective Electrical Rotation In Deg Angular Rotation:Between 5400.0 and 10800.0Center To Center Distance Between Terminals:0.200 inchesTerminal Location:Lower adjacent side single rowMounting Method:2.0 kilohms single section2.0 kilohms single sectionBetween 5400.0 and 10800.0Electrical Resistance Per Section:2.0 kilohms single sectionBetween 5400.0 and 10800.0Electrical Resistance Per Section:2.0 kilohms single sectionBetween 5400.0 and 10800.0Enter To Center Distance Between Center Terminal And Outside Terminal:0.100 inches	
0.080 inches         Body Length:         0.375 inches         Body Width:         0.170 inches         Body Height:         0.420 inches         Shaft Style:         Round, slotted         Actuator Type:         Single shaft         Effective Electrical Rotation In Deg Angular Rotation:         Between 5400.0 and 10800.0         Center To Center Distance Between Terminals:         0.200 inches         Terminal Location:         Lower adjacent side single row         Mounting Method:         Terminal         Electrical Resistance Per Section:         2.0 kilohms single section         Rotaty Actuator Travel In Angular Deg:         Between 5400.0 and 10800.0         Cheter To Center Distance Between Center Terminal And Outside Terminal:         0.100 inches	
Body Length:0.375 inchesBody Width:0.170 inchesBody Height:0.420 inches0.420 inchesShaft Style:Round, slottedActuator Type:Single shaftEffective Electrical Rotation In Deg Angular Rotation:Between 5400.0 and 10800.0Center To Center Distance Between Terminals:0.200 inchesTerminal Location:Location:Lower adjacent side single rowMounting Method:TerminalElectrical Resistance Per Section:2.0 kilchms single section2.0 kilchms single sectionBetween 5400.0 and 10800.0Entertical Resistance Der Section:2.0 kilchms no gale section2.0 kilchms no gale section2.0 kilchms no gale sectionBetween 5400.0 and 10800.0Forter To Center Distance Between Center Terminal And Outside Terminal:0.100 inches	-
0.375 inchesBody Widh:0.170 inchesBody Height:0.420 inches0.420 inchesShaft Style:Round, slottedActuator Type:Single shaftEffective Electrical Rotation In Deg Angular Rotation:Between 5400.0 and 10800.0Center To Center Distance Between Terminals:0.200 inchesTerminal Location:Lower adjacent side single rowMounting Method:TerminalPetrical Resistance Per Section:2.0 kilohms single sectionRotary Actuator Travel In Angular Deg:Between 5400.0 and 10800.0Center To Center Distance Between Center Terminal And Outside Terminal:0.100 inches	
Body Width:0.170 inchesBody Height:0.420 inches0.420 inchesShaft Style:Round, slottedActuator Type:Single shaftEffective Electrical Rotation In Deg Angular Rotation:Between 5400.0 and 10800.0Center To Center Distance Between Terminals:0.200 inchesTerminal Location:Lower adjacent side single rowMounting Method:2.0.0 kindms single section:2.0.0 kindms single sectionBetween 5400.0 and 10800.0Center To Center Distance Der Section:2.0.0 kindms single section2.0.0 kindms single section2.0.0 kindms single sectionBetween 5400.0 and 10800.0Center To Center Distance Between Center Terminal And Outside Terminal:0.100 inches	
0.170 inchesBody Height:0.420 inchesShaft Style:Round, slottedActuator Type:Single shaftEffective Electrical Rotation In Deg Angular Rotation:Between 5400.0 and 10800.0Center To Center Distance Between Terminals:0.200 inchesTerminal Location:Lower adjacent side single rowMounting Method:2.0 kilohms single section2.0 kilohms single section2.0 kilohms single sectionBetween 5400.0 and 10800.0Center To Center Distance Det Section:1.0 kilohms single section2.0 kilohms single section2.0 kilohms single sectionActuator Travel In Angular Deg:Between 5400.0 and 10800.0Center To Center Distance Between Center Terminal And Outside Terminal:0.100 inches	
Body Height:0.420 inches0.420 inchesShaft Style:Round, slottedActuator Type:Single shaftEffective Electrical Rotation In Deg Angular Rotation:Between 5400.0 and 10800.0Center To Center Distance Between Terminals:0.200 inchesTerminal Location:Lower adjacent side single rowMounting Method:TerminalElectrical Resistance Per Section:2.0 kilohms single section2.0 kilohms single sectionBetween 5400.0 and 10800.0Center To Center Distance Between Center Terminal And Outside Terminal:0.100 inches	-
0.420 inches Shaft Style: Round, slotted Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: Effective Electrical Rotation In Deg Angular Rotation: Between 5400.0 and 10800.0 Center To Center Distance Between Terminals: 0.200 inches Terminal Location: Lower adjacent side single row Mounting Method: Terminal Electrical Resistance Per Section: 2.0 kilohms single section Rotary Actuator Travel In Angular Deg: Between 5400.0 and 10800.0 Center To Center Distance Between Center Terminal And Outside Terminal: 0.100 inches	
Shaft Style:Round, slottedRound, slottedActuator Type:Single shaftEffective Electrical Rotation In Deg Angular Rotation:Between 5400.0 and 10800.0Center To Center Distance Between Terminals:0.200 inchesTerminal Location:Lower adjacent side single rowMounting Method:TerminalElectrical Resistance Per Section:2.0 kilohms single sectionRotary Actuator Travel In Angular Deg:Between 5400.0 and 10800.0Center To Center Distance Between Center Terminal And Outside Terminal:0.100 inches	
Round, slottedActuator Type:Single shaftEffective Electrical Rotation In Deg Angular Rotation:Between 5400.0 and 10800.0Center To Center Distance Between Terminals:0.200 inchesTerminal Location:Lower adjacent side single rowMounting Method:TerminalElectrical Resistance Per Section:2.0 kilohms single sectionRotary Actuator Travel In Angular Deg:Between 5400.0 and 10800.0Center To Center Distance Between Center Terminal And Outside Terminal:0.100 inches	
Actuator Type:Single shaftEffective Electrical Rotation In Deg Angular Rotation:Effective Electrical Rotation In Deg Angular Rotation:Between 5400.0 and 10800.0Center To Center Distance Between Terminals:0.200 inchesTerminal Location:Lower adjacent side single rowMounting Method:TerminalElectrical Resistance Per Section:2.0 kilohms single sectionRotary Actuator Travel In Angular Deg:Between 5400.0 and 10800.0Center To Center Distance Between Center Terminal And Outside Terminal:0.100 inches	
Single shaft Effective Electrical Rotation In Deg Angular Rotation: Between 5400.0 and 10800.0 Center To Center Distance Between Terminals: 0.200 inches Terminal Location: Lower adjacent side single row Mounting Method: Terminal Electrical Resistance Per Section: 2.0 kilohms single section Rotary Actuator Travel In Angular Deg: Between 5400.0 and 10800.0 Center To Center Distance Between Center Terminal And Outside Terminal: 0.100 inches	
Effective Electrical Rotation In Deg Angular Rotation:Between 5400.0 and 10800.0Center To Center Distance Between Terminals:0.200 inchesTerminal Location:Lower adjacent side single rowMounting Method:TerminalElectrical Resistance Per Section:2.0 kilohms single sectionRotary Actuator Travel In Angular Deg:Between 5400.0 and 10800.0Center To Center Distance Between Center Terminal And Outside Terminal:0.100 inches	Actuator Type:
Between 5400.0 and 10800.0Center To Center Distance Between Terminals:0.200 inchesTerminal Location:Lower adjacent side single rowMounting Method:TerminalElectrical Resistance Per Section:2.0 kilohms single sectionRotary Actuator Travel In Angular Deg:Between 5400.0 and 10800.0Center To Center Distance Between Center Terminal And Outside Terminal:0.100 inches	Single shaft
Center To Center Distance Between Terminals:0.200 inchesTerminal Location:Lower adjacent side single rowMounting Method:TerminalElectrical Resistance Per Section:2.0 kilohms single sectionRotary Actuator Travel In Angular Deg:Between 5400.0 and 10800.0Center To Center Distance Between Center Terminal And Outside Terminal:0.100 inches	Effective Electrical Rotation In Deg Angular Rotation:
0.200 inches Terminal Location: Lower adjacent side single row Mounting Method: Terminal Electrical Resistance Per Section: 2.0 kilohms single section Rotary Actuator Travel In Angular Deg: Between 5400.0 and 10800.0 Center To Center Distance Between Center Terminal And Outside Terminal: 0.100 inches	3etween 5400.0 and 10800.0
Terminal Location:Lower adjacent side single rowMounting Method:TerminalElectrical Resistance Per Section:2.0 kilohms single sectionRotary Actuator Travel In Angular Deg:Between 5400.0 and 10800.0Center To Center Distance Between Center Terminal And Outside Terminal:0.100 inches	Center To Center Distance Between Terminals:
Lower adjacent side single row Mounting Method: Terminal Electrical Resistance Per Section: 2.0 kilohms single section Rotary Actuator Travel In Angular Deg: Between 5400.0 and 10800.0 Center To Center Distance Between Center Terminal And Outside Terminal: 0.100 inches	).200 inches
Mounting Method:TerminalElectrical Resistance Per Section:2.0 kilohms single sectionRotary Actuator Travel In Angular Deg:Between 5400.0 and 10800.0Center To Center Distance Between Center Terminal And Outside Terminal:0.100 inches	Ferminal Location:
Terminal Electrical Resistance Per Section: 2.0 kilohms single section Rotary Actuator Travel In Angular Deg: Between 5400.0 and 10800.0 Center To Center Distance Between Center Terminal And Outside Terminal: 0.100 inches	ower adjacent side single row
Electrical Resistance Per Section: 2.0 kilohms single section Rotary Actuator Travel In Angular Deg: Between 5400.0 and 10800.0 Center To Center Distance Between Center Terminal And Outside Terminal: 0.100 inches	Nounting Method:
<ul> <li>2.0 kilohms single section</li> <li>Rotary Actuator Travel In Angular Deg:</li> <li>Between 5400.0 and 10800.0</li> <li>Center To Center Distance Between Center Terminal And Outside Terminal:</li> <li>0.100 inches</li> </ul>	Cerminal
Rotary Actuator Travel In Angular Deg:         Between 5400.0 and 10800.0         Center To Center Distance Between Center Terminal And Outside Terminal:         0.100 inches	Electrical Resistance Per Section:
Between 5400.0 and 10800.0 Center To Center Distance Between Center Terminal And Outside Terminal: 0.100 inches	2.0 kilohms single section
Center To Center Distance Between Center Terminal And Outside Terminal: 0.100 inches	Rotary Actuator Travel In Angular Deg:
0.100 inches	3etween 5400.0 and 10800.0
	Center To Center Distance Between Center Terminal And Outside Terminal:
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power	).100 inches
	Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section	50.0 single section
	Fempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:	50.0 to 50.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:	50.0 to 50.0 single section

# NSN 5905-00-448-5537

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



## Power Dissipation Rating Per Section In Watts:

0.75 free air single section

## **Resistance Tolerance Per Section In Percent:**

-5.0 to 5.0 single section

# Actuator Travel Control Feature:

Clutch

# Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

## Standard Taper Curve Per Section:

A single section

#### **Test Data Document:**

81349-mil-r-39015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

3 pin

### **Specification Data:**

81349-mil-r-39015/3 government specification

Shelf Life:

N/a

---

Unit Of Measure:

Demilitarization:

Deminitarization

No

Fiig:

A002a0