NSN 5905-00-448-9699

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-448-9699

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Overall Length:
0.460 inches
Terminal Length:
0.188 inches
Overall Height:
0.568 inches
Overall Width:
0.190 inches
Shaft Diameter:
0.093 inches
Shaft Length:
0.080 inches
Body Length:
0.380 inches
Body Width:
0.190 inches
Body Height:
0.380 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
8280.0
Maximum Starting Torque:
5.00 inch-ounces
Maximum Running Torque:
5.00 inch-ounces
Center To Center Distance Between Terminals:
0.200 inches
Terminal Location:
Lower adjacent side two rows
Mounting Method:
Terminal
Center To Center Distance Between Terminal Rows:
0.100 inches

NSN 5905-00-448-9699 Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
560.0 ohms single section
Rotary Actuator Travel In Angular Deg:
3280.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
50.0 to 50.0 single section
Power Dissipation Rating Per Section In Watts:
0.75 free air single section
Resistance Tolerance Per Section In Percent:
5.0 to 5.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
35.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A002a0