NSN 5905-00-450-5172

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-450-5172

| Continu Overstitus | | | | | | |
|---|--|--|--|--|--|--|
| Section Quantity: | | | | | | |
| 1 | | | | | | |
| Body Style: | | | | | | |
| Cylindrical Polichilita Indicator | | | | | | |
| Reliability Indicator: | | | | | | |
| Not established | | | | | | |
| Overall Length: | | | | | | |
| 0.703 inches | | | | | | |
| Body Diameter: | | | | | | |
| 0.785 inches | | | | | | |
| Body Length: | | | | | | |
| 0.422 inches | | | | | | |
| Actuator Type: | | | | | | |
| Flush drive with slot-hole | | | | | | |
| Effective Electrical Rotation In Deg Angular Rotation: | | | | | | |
| 246.0 | | | | | | |
| Terminal Location: | | | | | | |
| Front end | | | | | | |
| Mounting Method: | | | | | | |
| Tab | | | | | | |
| Features Provided: | | | | | | |
| Grounded contact arm | | | | | | |
| Electrical Resistance Per Section: | | | | | | |
| 5.0 kilohms single section | | | | | | |
| Rotary Actuator Travel In Angular Deg: | | | | | | |
| 246.0 | | | | | | |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: | | | | | | |
| 105.0 single section | | | | | | |
| Power Dissipation Rating Per Section In Watts: | | | | | | |
| 1.5 free air single section | | | | | | |
| Resistance Tolerance Per Section In Percent: | | | | | | |
| -10.0 to 10.0 single section | | | | | | |
| Actuator Travel Control Feature: | | | | | | |
| Stops | | | | | | |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: | | | | | | |
| 55.0 single section | | | | | | |
| Standard Taper Curve Per Section: | | | | | | |
| A single section | | | | | | |
| Terminal Type And Quantity: | | | | | | |
| 2 tab, solder lug | | | | | | |
| Shelf Life: | | | | | | |
| | | | | | | |

N/a

NSN 5905-00-450-5172

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|-----|-----|------|
| In | 18 | <i>(</i>)+ | МЛО | 201 | ure: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A002a0