## NSN 5905-00-450-8762

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-450-8762

Electrical Resistance:  1.920 kilohms  Resistance Tolerance In Percent:  1.000/41.000  Ambient Tempurature In Deg Celsius At Full Rated Power:  170.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  1850.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  1850.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  1850.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  1850.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  1850.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  1850.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  1850.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  1850.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  1850.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  1850.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  1850.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  1850.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  1850.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  1850.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  1850.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  1850.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  1850.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  1850.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  1850.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  1850.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  1850.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  1850.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  1850.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  1850.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  1850.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  1850.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  1850.0  Te	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: 1.000/4.1000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/470.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Body Diameter: 0.196 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Avail terminal each end Test Data Document: 106419-910110 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Via Unit Of Measure:	-500.0/+500.0
Resistance Tolerance in Percent: 1.000/+1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 1.000/+1.000 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 1.50.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 1.50.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 1.50.0/+70.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 1.50.0/+70.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 1.50.0/+70.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 1.50.0/+70.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 1.50.0/+70.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 1.50.0/+70.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 1.50.0/+70.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 1.50.0/+70.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 1.50.0/+70.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 1.50.0/+70.0 Tempurature Range Of Tempurature Range Ra	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power:  70.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0+70.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Body Diameter:  0.196 inches  Body Length:  0.562 inches  Power Dissipation Rating In Watts:  1.550 ree air  Skyle Designator:  Availaterminal each end  Test Data Document:  0.6481-910110 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  Wa  Unit Of Measure:  — Demilitarization:  No  Filig:	3.920 kilohms
Ambient Tempurature In Deg Celsius At Full Rated Power:  70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius:  155.0/470.0 Inclosure Method: Encapsulated Terminal Type:  Wire lead Body Diameter:  0.196 inches Body Length:  0.562 inches Power Dissipation Rating In Watts:  0.300 free air  Style Designator:  Axial terminal each end Test Data Document:  106481-910110 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;  excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  Wa Unit Of Measure:  — Demilitarization:  No Filig:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  155.0/+70.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Body Diameter:  0.196 inches  Body Length:  0.562 inches  Power Dissipation Rating In Watts:  0.300 free air  Style Designator:  Avial terminal each end  Test Data Document:  106481-910110 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  Wa  Unit Of Measure:  Demilitarization:  No  Filig:	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/470.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Body Diameter:  0.196 inches  Body Length:  0.562 inches  Power Dissipation Rating In Watts:  0.500 free air  Style Designator:  Axial terminal each end  Test Data Document:  0.6481-910110 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  Wa  Unit Of Measure:  Demilitarization:  No  Filig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Information Range Of Tempurature Coefficient In Deg Celsius: 155.0/+70.0 Inclosure Method: Incapsulated Incap	70.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+70.0  Inclosure Method: Encapsulated  Ferminal Type:  Wire lead  Body Diameter:  0.196 inches  Body Length:  0.562 inches  Power Dissipation Rating In Watts:  0.500 free air  Style Designator:  Avial terminal each end  Fest Data Document:  0.6481-910110 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  Included Test Data Document:  Other Data Document	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
inclosure Method: Encapsulated Ferminal Type: Wire lead Body Diameter: 0.196 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Fest Data Document: 0.6481-910110 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life:  Unit Of Measure:  Demilitarization: No Filig:	150.0
Inclosure Method: Encapsulated Ferminal Type: Wire lead Body Diameter: 0.196 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Fest Data Document: 06481-910110 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Ferminal Type: Wire lead Body Diameter: 0.196 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Fest Data Document: 06481-910110 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	-55.0/+70.0
Terminal Type:  Wire lead  Body Diameter:  D.196 inches  Body Length: D.5062 inches  Power Dissipation Rating In Watts: D.500 free air  Style Designator: Axial terminal each end  Test Data Document: D6481-910110 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	Inclosure Method:
Wire lead  Body Diameter:  D.196 inches  Body Length: D.5062 inches  Power Dissipation Rating In Watts: D.500 free air  Style Designator: Axial terminal each end  Test Data Document: D6481-910110 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	Encapsulated
Body Diameter: 0.196 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 0.6481-910110 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	Terminal Type:
20.196 inches  Body Length: 20.562 inches  Power Dissipation Rating In Watts: 20.500 free air  Style Designator:  Axial terminal each end  Test Data Document: 20.6481-910110 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 20.500 excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  W/a  Unit Of Measure:  Demilitarization:  No  Fiig:	Wire lead
Body Length: 0.562 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Fest Data Document: 06481-910110 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Body Diameter:
Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 0.6481-910110 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.196 inches
Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Fest Data Document: 0.6481-910110 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Body Length:
D.500 free air  Style Designator:  Axial terminal each end  Test Data Document:  D6481-910110 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	0.562 inches
Style Designator: Axial terminal each end  Test Data Document: D6481-910110 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  V/a  Unit Of Measure:  Demilitarization: No  Filig:	Power Dissipation Rating In Watts:
Axial terminal each end  Test Data Document:  D6481-910110 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	0.500 free air
Test Data Document:  06481-910110 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	Style Designator:
D6481-910110 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	06481-910110 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
N/a Unit Of Measure: Demilitarization: No Fiig:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Filg:	Unit Of Measure:
No Filg:	<del></del>
Fiig:	Demilitarization:
	No
N001a0	Fiig:
	A001a0