NSN 5905-00-451-1043

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-451-1043

Section Overtitus
Section Quantity:
1 Partic Studen
Body Style:
Rectangular
Reliability Indicator:
Not established
Terminal Length: 0.172 inches
Shaft Diameter:
0.078 inches
Shaft Length:
0.045 inches
Body Length:
0.540 inches
Body Width:
0.205 inches
Body Height:
0.500 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Center To Center Distance Between Terminals:
0.200 inches
Terminal Location:
Lower adjacent side single row
Mounting Method:
Terminal
Electrical Resistance Per Section:
1.0 kilohms single section
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0 to 50.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section

NSN 5905-00-451-1043

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



A single section

Special Features:

W/gold @plated printed circuit pin terminals

Test Data Document:

10236-7010026 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0