NSN 5905-00-451-1853

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-451-1853

Section Quantity:

1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
1.203 inches
Body Diameter:
1.249 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.750 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.453 inches
Overall Diameter:
0.938 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
300.0
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.438 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Offici
Screw Thready Qty Per Inch (tpi):
Screw Thready Qty Per Inch (tpi):
Screw Thready Qty Per Inch (tpi): 32.0
Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location:
Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Lower adjacent side single row

500.000 kilohms single section

NSN 5905-00-451-1853

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
300.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Power Dissipation Rating Per Section In Watts:
5.0 free air single section
Resistance Tolerance Per Section In Percent:
-30.0 to 30.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig: