## NSN 5905-00-451-4325

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-451-4325 **Section Quantity: Reliability Indicator:** Not established **Mounting Hole Diameter:** 0.075 inches **Shaft Diameter:** 0.035 inches **Shaft Length:** 0.060 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Lateral Distance Between Mounting Hole Centers:** Between 0.513 inches and 0.526 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Right adjacent side from adjustment control **Mounting Method:** Unthreaded holes and pins **Electrical Resistance Per Section:** 500.000 kilohms single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0 to 100.0 single section **Power Dissipation Rating Per Section In Watts:** 0.75 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5905-00-451-4325

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



_		••	• -				
1	em		ゖっ	riz	<b>2</b> †1	n	
_			ıιa	114	au	VII	١.

No

Fiig:

A002a0