NSN 5905-00-451-5690

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-451-5690 **Section Quantity: Body Style:** Cylindrical friction mounted **Reliability Indicator:** Not established **Body Diameter:** 3.500 inches **Shaft Diameter:** 0.249 inches **Shaft Length:** 0.940 inches **Body Length:** 5.000 inches **Shaft Style:** Round **Actuator Type:** Double ended shaft **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Clamp ring **Electrical Resistance Per Section:** 10.000 kilohms 3rd section **Rotary Actuator Travel In Angular Deg:** 335.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 all sections **Power Dissipation Rating Per Section In Watts:** 5.0 free air all sections **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 all sections **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 all sections **Standard Taper Curve Per Section:** A all sections **Terminal Type And Quantity:** 18 turret Shelf Life:

N/a

NSN 5905-00-451-5690

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0