## NSN 5905-00-451-7307

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-451-7307

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Overall Length:
1.062 inches
Terminal Length:
0.500 inches
Overall Height:
0.500 inches
Overall Width:
0.312 inches
Body Length:
0.562 inches
Body Width:
0.312 inches
Body Height:
0.500 inches
Actuator Type:
Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
320.0
Maximum Starting Torque:
7.50 inch-ounces
Maximum Running Torque:
0.25 inch-ounces
Maximum Stop Torque:
30.00 inch-ounces
Center To Center Distance Between Terminals:
0.200 inches
Terminal Location:
Front end
Mounting Method:
Terminal
Electrical Resistance Per Section:
5.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
320.0
Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

## NSN 5905-00-451-7307

No Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-150.0 to 150.0 single section
Power Dissipation Rating Per Section In Watts:
0.75 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: