NSN 5905-00-452-9184

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-452-9184 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.0000 inches Pilot Length: 0.0620 inches **Undercut Diameter:** 1.000 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 1.0625 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.5625 inches **Body Length:** 0.9531 inches **Mounting Lip Diameter:** 1.0625 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 360.0 **Terminal Location:** Rear end **Mounting Method:** Clamp ring

Electrical Resistance Per Section: 150.0 ohms single section

Rotary Actuator Travel In Angular Deg:

360.0

Resistance Tolerance Per Section In Percent:

-1.0 to 1.0 single section

NSN 5905-00-452-9184

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:
Continuous motion
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0