

View Online at <https://aerobasegroup.com/nsn/5905-00-452-9186>

**Section Quantity:**

1

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

Between 0.9995 inches and 1.0000 inches

**Pilot Length:**

Between 0.0590 inches and 0.0620 inches

**Undercut Diameter:**

Between 0.9995 inches and 1.0000 inches

**Undercut Width:**

0.0500 inches

**Body Diameter:**

Between 1.059 inches and 1.062 inches

**Shaft Diameter:**

0.120 inches

**Shaft Length:**

0.562 inches

**Body Length:**

0.938 inches

**Mounting Lip Diameter:**

Between 1.0590 inches and 1.0620 inches

**Mounting Lip Depth:**

0.0950 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Double ended shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

355.0

**Terminal Location:**

Rear end

**Mounting Method:**

Clamp ring

**Electrical Resistance Per Section:**

10.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

360.0

**Function Conformity Tolerance Per Section:**

-0.25/+0.25 single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

150.0 single section

**Power Dissipation Rating Per Section In Watts:**

1.5 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Actuator Travel Control Feature:**

Stops

**Function Characteristic Per Section:**

Single section linear

**Terminal Type And Quantity:**

3 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0