NSN 5905-00-455-0271

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-455-0271 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes **Overall Length:** 0.410 inches **Terminal Length:** 5.000 inches **Overall Height:** 0.375 inches **Overall Width:** Between 0.208 inches and 0.218 inches **Mounting Hole Diameter:** Between 0.061 inches and 0.063 inches **Shaft Diameter:** Between 0.072 inches and 0.076 inches **Shaft Length:** 0.030 inches **Body Length:** 0.375 inches **Body Width:** Between 0.208 inches and 0.218 inches **Body Height:** 0.375 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 360.0 **Lateral Distance Between Mounting Hole Centers:** 0.375 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Electrical Resistance Per Section:**

1.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 360.0

NSN 5905-00-455-0271

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -50.0 to 50.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Actuator Travel Control Feature:** Continuous motion Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 50.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 wire lead Shelf Life: N/a **Unit Of Measure: Demilitarization:** No