

View Online at <https://aerobasegroup.com/nsn/5905-00-456-1901>

**Temperature Coefficient Of Resistance In Ppm Per Deg Celsius:**

-50.0/+50.0

**Electrical Resistance:**

73.200 kilohms

**Resistance Tolerance In Percent:**

-1.000/+1.000

**Ambient Temperature In Deg Celsius At Full Rated Power:**

125.0

**Ambient Temperature In Deg Celsius At Zero Percent Rated Power:**

175.0

**Temperature Range Of Temperature Coefficient In Deg Celsius:**

-55.0/+175.0

**Inclosure Method:**

Hermetically sealed

**Terminal Type:**

Wire lead

**Reliability Indicator:**

Established

**Reliability Failure Rate Level In Percent:**

0.001

**Body Diameter:**

0.109 inches

**Body Length:**

0.250 inches

**Power Dissipation Rating In Watts:**

0.100 free air

**End Application:**

Ticonderoga class cg (47); support equipment, b-52 aircraft; submarine miscellaneous sonar and adp systems; missile, minuteman lgm-30; helicopter, carrier based asw, sh-60f; arleigh burke class ddg; mk-6, mod 0 optical sight; aircraft, strato fortress b-52; chaparral/vulcan ads/ssamd

**Criticality Code Justification:**

Feat

**Special Features:**

Weapon system essential

**Style Designator:**

Axial terminal each end

**Test Data Document:**

81349-mil-prf-55182/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-prf-55182/1 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

**Demilitarization:**

No

**Fiig:**

A001a0

**Mil-std (military Standard):**

Mil-prf-55182 spec.