NSN 5905-00-457-0976

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-457-0976
Section Quantity:
1
Body Style:
Cylindrical
Reliability Indicator:
Not established
Body Diameter:
0.312 inches
Body Length:
0.180 inches
Actuator Type:
Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
300.0
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Terminal
Electrical Resistance Per Section:
20.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
300.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Resistance Tolerance Per Section In Percent:
-30.0 to 30.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5905-00-457-0976

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Fiig:

A002a0