NSN 5905-00-457-2970

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-457-2970

Section Quantity:
1
Body Style:
Rectangular w/bushing
Reliability Indicator:
Not established
Shaft Diameter:
0.180 inches
Shaft Length:
0.250 inches
Mounting Bushing Length:
0.250 inches
Body Length:
1.312 inches
Body Width:
0.266 inches
Body Height:
0.391 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
7920.0
Screw Thread Diameter:
0.190 inches
Screw Thread Series Designator:
Unf
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear end
Mounting Method:
Standard bushing w/panel seal
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
10.950 kilohms single section
Rotary Actuator Travel In Angular Deg:
7920.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
475 O single postion

175.0 single section

NSN 5905-00-457-2970

Demilitarization:

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -30.0 to 30.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 wire lead Shelf Life: N/a **Unit Of Measure:**