Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-458-4423

Section Quantity: 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.320 inches **Terminal Length:** Between 0.469 inches and 0.531 inches Mounting Hole Diameter: Between 0.088 inches and 0.098 inches Shaft Diameter: 0.115 inches Shaft Length: 0.070 inches **Body Length:** Between 1.240 inches and 1.260 inches **Body Width:** Between 0.180 inches and 0.200 inches **Body Height:** Between 0.300 inches and 0.330 inches Shaft Style: Round, slotted Actuator Type: Single shaft **Center To Center Distance Between Terminals:** Between 0.890 inches and 0.910 inches **Fragility Factor:** Moderately rugged Lateral Distance Between Mounting Hole Centers: Between 0.995 inches and 1.005 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Lower adjacent side single row Mounting Method: Unthreaded hole and terminal **Cubic Measure:** 0.079 cubic inches **Electrical Resistance Per Section:** 

50.0 ohms single section

## NSN 5905-00-458-4423

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



**Rotary Actuator Travel In Angular Deg:** Between 6120.0 and 9720.0 Center To Center Distance Between Center Terminal And Outside Terminal: Between 0.690 inches and 0.710 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -250.0 to 250.0 single section **Power Dissipation Rating Per Section In Watts:** 0.75 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section **Standard Taper Curve Per Section:** A single section **Test Data Document:** 81349-mil-r-22097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 3 pin **Specification Data:** 81349-mil-r-22097/2 government specification Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A002a0