

View Online at <https://aerobasegroup.com/nsn/5905-00-458-7141>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

2.125 inches

Terminal Length:

Any acceptable

Body Diameter:

0.938 inches

Shaft Diameter:

0.275 inches

Shaft Length:

0.875 inches

Mounting Bushing Length:

0.375 inches

Body Length:

0.875 inches

Overall Diameter:

0.938 inches

Undercut Diameter:

0.187 inches

Shaft Style:

Round, stepped

Shaft Bearing Type:

Bearing

Actuator Type:

Single shaft

Nonturn Device Location:

At 6 oclock

Nonturn Device Radius:

0.438 inches

Center To Center Distance Between Terminals:

0.200 inches

Undercut Length:

0.500 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Rear end

Mounting Method:

Standard bushing and clamp ring

Electrical Resistance Per Section:

25.0 kilohms 2nd section

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Power Dissipation Rating Per Section In Watts:

0.5 free air 1st section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 all sections

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

55.0 all sections

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

6 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0