## NSN 5905-00-458-8351

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-458-8351 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.750 inches **Terminal Length:** 11.500 inches **Overall Height:** 0.328 inches **Overall Width:** 0.250 inches **Mounting Hole Diameter:** 0.087 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.500 inches **Body Length:** 1.250 inches **Body Width:** 0.250 inches **Body Height:** 0.328 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Lateral Distance Between Mounting Hole Centers:** 1.000 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:** 

Unthreaded hole
Features Provided:
Nonmetallic shaft

**Electrical Resistance Per Section:** 

500.000 ohms single section

## NSN 5905-00-458-8351

A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



## **Rotary Actuator Travel In Angular Deg:** 360.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 200.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -50.0 to 50.0 single section **Power Dissipation Rating Per Section In Watts:** 5.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Actuator Travel Control Feature:** Continuous motion Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 wire lead Shelf Life: N/a **Unit Of Measure:** Demilitarization: No Fiig: