NSN 5905-00-459-1776

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-459-1776 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.810 inches **Body Diameter:** 0.500 inches **Shaft Diameter:** 0.281 inches **Shaft Length:** 0.690 inches **Mounting Bushing Length:** 0.240 inches **Body Length:** 1.000 inches **Overall Diameter:** 0.500 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 0.80 inch-ounces **Maximum Running Torque:** 0.60 inch-ounces **Maximum Stop Torque:** 20.00 inch-ounces **Shaft End Play:** 0.010 inches **Shaft Radial Play:** 0.003 inches **Screw Thread Diameter:**

Screw Thread Series Designator:

0.250 inches

Unef

NSN 5905-00-459-1776

Precision Wire Wound Variable Resistor - Page 2 of 2



Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear end
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
1.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.30/+0.30 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Test Data Document:
08241-ds101267 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
3 solder stud
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A002a0