NSN 5905-00-459-2535

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-459-2535

Electrical Resistance: 0.200 ohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -85.04/275.0 Inclosure Method: Encased Terminal Type: -Tab. solder lug Reliability Indicator: Established Reliability Indicator: Established Reliability Failure Rate Level in Percent: 0.010 Terminal Length: 0.438 inches Body Length: 1.338 inches Body Length: 1.338 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.626 inches Power Dissipation Rating in Watts: 10.000 free air Mounting Hole Size: 0.125 inches Style Designator: Axial terminal (s) Fest Data Document: 81349-mill-73909 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", 'average', ", etc.).	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance in Percent: -1.000/+1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+275.0 Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Established Reliability Failure Rate Level in Percent: 0.010 Terminal Length: 0.438 inches Body Length: 1.938 inches Body Length: 0.594 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating in Watts: 10.000 free air Mounting Hole Size: 0.125 inches Style Designator: Axial terminal (s) Test Data Document: 81349-mil+7-33009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).	-100.0/+100.0
Resistance Tolerance in Percent: -1.000/+1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+275.0 Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Established Reliability Failure Rate Level in Percent: 0.010 Terminal Length: 0.438 inches Body Length: 1.938 inches Body Width: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.552 inches Power Dissipation Rating in Watts: 10.000 free air Mounting Hole Size: 0.125 inches Style Designator: Axial terminal (s) Test Data Document: 81349-mile-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	Electrical Resistance:
-1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.04-275.0 Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 0.438 inches Body Length: 1.338 inches Body Length: 1.338 inches Body Width: 0.594 inches Body Width: 0.595 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.552 inches Power Dissipation Rating In Watts: 1.0000 free air Mounting Hole Size: 0.125 inches Style Designator: Axial terminal (s) Test Data Document: 814349-milt-739009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	0.200 ohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 0.438 inches Body Length: 1.398 inches Body Length: 0.594 inches Body Width: 0.594 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 10.000 fiee air Mounting Hole Size: 0.125 inches Style Designator: Axial terminal (s) Test Data Document: 81349-milt-739009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Established Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 0.438 inches Body Length: 1.938 inches Body Length: 1.938 inches Body Height: 0.594 inches Body Height: 0.626 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 0.150 inches Style Designator: Axial terminal (s) Test Data Document: 81349-milr-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 0.438 inches Body Length: 1.938 inches Body Width: 0.594 inches Body Width: 0.525 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating in Watts: 10.000 free air Mounting Hole Size: 0.125 inches Style Designator: Axial terminal (s) Test Data Document: 81349-milr-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -56.04-275.0 Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 0.438 inches Body Length: 1.938 inches Body Length: 1.938 inches Body Width: 0.626 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 10.000 free air Mounting Hole Size: 0.125 inches Style Designator: Axial terminal (s) Test Data Document: 81349-milt-739009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	25.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -56.04-275.0 Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 0.438 inches Body Length: 1.938 inches Body Length: 1.938 inches Body Width: 0.626 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 10.000 free air Mounting Hole Size: 0.125 inches Style Designator: Axial terminal (s) Test Data Document: 81349-milt-739009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
-55.0/+275.0 Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 0.438 inches Body Length: 1.938 inches Body Length: 0.594 inches Body Width: 0.594 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 10.000 free air Mounting Hole Size: 0.125 inches Style Designator: Axial terminal (s) Test Data Document: 81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).	275.0
Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 0.438 inches Body Length: 1.938 inches Body Width: 0.594 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 10.000 free air Mounting Hole Size: 0.125 inches Style Designator: Axial terminal (s) Test Data Document: 81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encased Terminal Type: Tab, solder lug Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 0.0438 inches Body Length: 1.938 inches Body Width: 0.594 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 10.000 free air Mounting Hole Size: 0.125 inches Style Designator: Axial terminal (s) Test Data Document: 81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	-55.0/+275.0
Terminal Type: Tab, solder lug Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 0.438 inches Body Length: 1.938 inches Body Width: 0.594 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Distance Between Stating In Watts: 10.000 free air Mounting Hole Size: 0.125 inches Style Designator: Axial terminal (s) Test Data Document: 11349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	Inclosure Method:
Tab, solder lug Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 0.438 inches Body Length: 1.938 inches Body Width: 0.594 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 10.000 free air Mounting Hole Size: 0.125 inches Style Designator: Axial terminal (s) Test Data Document: 81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	Encased
Tab, solder lug Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 0.438 inches Body Length: 1.938 inches Body Width: 0.594 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 10.000 free air Mounting Hole Size: 0.125 inches Style Designator: Axial terminal (s) Test Data Document: 81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	Terminal Type:
Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 0.438 inches Body Length: 1.938 inches Body Width: 0.594 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 10.000 free air Mounting Hole Size: 0.125 inches Style Designator: Axial terminal (s) Test Data Document: 81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	Tab, solder lug
Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 0.438 inches Body Length: 1.938 inches Body Width: 0.594 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 10.000 free air Mounting Hole Size: 0.125 inches Style Designator: Axial terminal (s) Test Data Document: 81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	Reliability Indicator:
Terminal Length: 0.438 inches Body Length: 1.938 inches Body Width: 0.594 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Distance Between Rating In Watts: 1.562 inches Power Dissipation Rating In Watts: 10.000 free air Mounting Hole Size: 0.125 inches Style Designator: Axial terminal (s) Test Data Document: 81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Terminal Length: 0.438 inches Body Length: 1.938 inches Body Width: 0.594 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Distance Between Rating In Watts: 1.562 inches Power Dissipation Rating In Watts: 10.000 free air Mounting Hole Size: 0.125 inches Style Designator: Axial terminal (s) Test Data Document: 81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	Reliability Failure Rate Level In Percent:
Body Length: 1.938 inches Body Width: 0.594 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 10.000 free air Mounting Hole Size: 0.125 inches Style Designator: Axial terminal (s) Test Data Document: 81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	0.010
Body Length: 1.938 inches Body Width: 0.594 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 10.000 free air Mounting Hole Size: 0.125 inches Style Designator: Axial terminal (s) Test Data Document: 81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	Terminal Length:
1.938 inches Body Width: 0.594 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 10.000 free air Mounting Hole Size: 0.125 inches Style Designator: Axial terminal (s) Test Data Document: 81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	0.438 inches
1.938 inches Body Width: 0.594 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 10.000 free air Mounting Hole Size: 0.125 inches Style Designator: Axial terminal (s) Test Data Document: 81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	Body Length:
Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 10.000 free air Mounting Hole Size: 0.125 inches Style Designator: Axial terminal (s) Test Data Document: 81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	1.938 inches
Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 10.000 free air Mounting Hole Size: 0.125 inches Style Designator: Axial terminal (s) Test Data Document: 81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	Body Width:
0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 10.000 free air Mounting Hole Size: 0.125 inches Style Designator: Axial terminal (s) Test Data Document: 81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	0.594 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 10.000 free air Mounting Hole Size: 0.125 inches Style Designator: Axial terminal (s) Test Data Document: 81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	Body Height:
Power Dissipation Rating In Watts: 10.000 free air Mounting Hole Size: 0.125 inches Style Designator: Axial terminal (s) Test Data Document: 81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	0.625 inches
Power Dissipation Rating In Watts: 10.000 free air Mounting Hole Size: 0.125 inches Style Designator: Axial terminal (s) Test Data Document: 81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
Mounting Hole Size: 0.125 inches Style Designator: Axial terminal (s) Test Data Document: 81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	1.562 inches
Mounting Hole Size: 0.125 inches Style Designator: Axial terminal (s) Test Data Document: 81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	Power Dissipation Rating In Watts:
0.125 inches Style Designator: Axial terminal (s) Test Data Document: 81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	10.000 free air
Style Designator: Axial terminal (s) Test Data Document: 81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	Mounting Hole Size:
Axial terminal (s) Test Data Document: 81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	0.125 inches
Test Data Document: 81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	Style Designator:
81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	Axial terminal (s)
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
	Specification Data:
81349-mil-r-39009/1 government specification	81349-mil-r-39009/1 government specification

N/a

Shelf Life:

NSN 5905-00-459-2535

Inductive Wire Wound Fixed Resistor - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A001a0