Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-460-5008

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

## **Body Diameter:**

0.968 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

0.375 inches

Mounting Bushing Length:

0.250 inches

#### Body Length:

0.750 inches

#### Shaft Style:

Round, slotted

#### Shaft Bearing Type:

Sleeve

#### Switch Type:

Rotary

### Switch Voltage Rating In Volts:

125.0

#### Actuator Type:

Single shaft

### Switch Operating Position:

Start of rotation

### Switch Contact Arrangement:

Single pole, single throw, normally open, both positions maintained

#### Screw Thread Diameter:

0.375 inches

### Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

### **Terminal Location:**

Rear-bottom

#### **Mounting Method:**

Standard bushing

### **Electrical Resistance Per Section:**

5.0 kilohms single section



Power Dissipation Rating Per Section In Watts:

0.5 free air single section

#### **Resistance Tolerance Per Section In Percent:**

-20.0 to 20.0 single section

## Switch Current Type And Rating In Amps:

3.000 ac/dc

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A002a0